



PRESSURE

Explosion-Proof Gauge Pressure Transmitter

Tek-Bar 3120A



1 FEATURES

- Operator can calibrate device using zero/span button, no handheld calibrator required
- High accuracy up to $\pm 0.075\%$
- Various Output: 4-20 mA, digital signals
- EEPROM write protection
- Fail-safe mode process function for detecting any abnormal condition occurring
- The mounting bracket can be rotated up to 360° and LCD display up to 270°
- Automatic ambient temperature compensation improve performance of device

3 APPLICATIONS

- Distilleries
- Water and waste water industries
- Oil and Gas
- Pulp and Paper
- Dairy industries

CONTACT US

796 Tek Drive, Crystal Lake, IL 60014 USA

+1 847 857 6076
+1 847 655 7428

Email: tektrol@tek-trol.com

www.tek-trol.com

2 SPECIFICATION

Accuracy	$\pm 0.075\%$ of F.S.
Rangeability	50:1 turn down
Maximum working pressure limit	8100 PSI
Process temperature limits	-40 °F to +284 °F (-40 °C to 120 °C)
Stability	$\pm 0.125\%$ URL for 36 months
Ambient temperature effect	$\pm [0.019\% \text{URL} + 0.125\% \text{Span}] / 82.4 \text{ } ^\circ\text{F}$
Ambient temperature	-40 °F to +185 °F (-40 °C to 85 °C)
Humidity limits	5% to 100% RH
Power supply effects	$\pm 0.005\%$ of Span per Volt
Enclosure Rating	NEMA 4X (IP66) and explosion-proof for Class I, Div I
Display	5 digit LCD display
Damping time	0.25 to 60 sec
Failure mode	Fail High: Current $\geq 21.1 \text{ mA}$ Fail Low: Current $\leq 3.78 \text{ mA}$
Power supply	12 to 45 VDC
Weight	3.43 lb (1.56 kg)
Output signal	4 mA to 20 mA with HART®
Isolation	500 Vrms (707 VDC)
HART loop resistance	250 to 550 ohm
Process connection size	1/2" NPT female
Electrical connections	1/2" NPT female
2" Pipe stanchion type bracket	Angle or flat type
Approvals	NEMA 4X (IP66) and FM (Class I Div I)
Bolts and bolting flange	304SST
Electronic housing	Aluminum (Option:316SST)
Mounting bracket	304SST with U-bolt (304SST) for 2" pipe
Paint	Epoxy-Polyester or Polyuret
Fill fluid	Silicone oil or inert fill
Wetted materials	Hastelloy-C Diaphragm
Isolating diaphragm	316SST