

# Brass Case, Liquid Filled



## 300 SERIES

- High quality, heavy-duty liquid filled gauge
- Vacuum and compound ranges through 0 psi to 15,000 psi
- 2-1/2" and 4" gauge sizes
- Die cast Brass case with natural Brass finish
- Copper alloy or 316 Stainless Steel and Brass wetted parts

### OPERATING SPECIFICATIONS

#### 1. Working Pressure Limitations

##### a. Dynamic Pressure

The working pressure should be limited to 60% of the dial range.

##### b. Static Pressure

The working pressure, where no sharp fluctuations occur, should be limited to 90% of the dial range.

### APPLICATIONS

- Automotive
- Construction
- Hydraulics & pneumatics
- Mining
- Stamping & forming presses
- Transportation

	SERIES	SPECIFICATIONS
Pressure ranges	300 Series (all)	Vacuum and compound ranges through 0 psi to 15,000 psi
Accuracy	25-300, 25-310	±1.6% full scale
	40-300, 40-310	± 1% full scale
Temperature ranges*	300 Series (all)	Media -4 °F to 140 °F (-20 °C to 60 °C) Ambient 0 °F to 160 °F (-18 °C to 71 °C) Optional temperature ratings available from -40 °F to 212 °F (-40 °C to 100 °C)
Measuring element	25-300, 25-310 (≤ 600 psi)	Copper alloy "C" tube
	25-300, 25-310 (800 psi to 6,000 psi)	Copper alloy coiled safety tube
	25-300, 25-310 (7,500 psi to 15,000 psi)	316 Stainless Steel coiled safety tube
	40-300, 40-310 (≤ 1,000 psi)	Copper alloy "C" tube
	40-300, 40-310 (15,000 psi)	316 Stainless Steel coiled safety tube
Connection	25-300, 25-310	1/4" NPT die-cast Brass with the case. 7/16" – 20 SAE adjustable type straight thread with FKM O-ring is also available as a stock option on many ranges (-4 SAE).
	40-300, 40-310	1/4" NPT die-cast Brass with the case. 1/2" NPT is available on certain 40-300 ranges as a stock option, and on all other 40-300 and 40-310's as a non-stock option.
Case	300 Series (all)	Die cast Brass (natural Brass finish) with safety relief plug
Cover ring	300 Series (all)	Polished Brass
Lens	300 Series (all)	Acrylic with o-ring seal
Pointer	300 Series (all)	Balanced Aluminum, black finish
Dial	300 Series (all)	Aluminum, white background with black scale. UV resistant.
Movement	300 Series (all)	Brass and Nickel-silver with highly polished bearing surfaces
Fill liquid**	300 Series (all)	Glycerin

\* For every 18 °F (10 °C) shift in temperature from which the gauge is calibrated, the user can experience up to ±0.4% additional error.

\*\*See page 51 for gauge fill options.

For details on accuracy/standard dial configuration and dial layouts, see pages 56-61.




**WARNING:** This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

ORDERING INFORMATION						
<b>GAUGE SIZES</b>	<b>25</b> 2-1/2"	<b>40</b> 4"				
<b>CASE TYPES</b>	<b>300</b> Brass, bottom connection	<b>310</b> Brass, back connection				
<b>PRESSURE RANGES</b>	<b>30vac</b> -30 inHg to 0 psi	<b>30/300</b> -30 inHg to 0 to 300 psi	<b>300</b> 0 psi to 300 psi	<b>3000</b> 0 psi to 3,000 psi		
	<b>30/15</b> -30 inHg to 0 to 15 psi	<b>15</b> 0 psi to 15 psi	<b>400</b> 0 psi to 400 psi	<b>5000</b> 0 psi to 5,000 psi		
	<b>30/30</b> -30 inHg to 0 to 30 psi	<b>30</b> 0 psi to 30 psi	<b>600</b> 0 psi to 600 psi	<b>6000</b> 0 psi to 6,000 psi		
	<b>30/60</b> -30 inHg to 0 to 60 psi	<b>60</b> 0 psi to 60 psi	<b>800</b> 0 psi to 800 psi	<b>7500</b> 0 psi to 7,500 psi		
	<b>30/100</b> -30 inHg to 0 to 100 psi	<b>100</b> 0 psi to 100 psi	<b>1000</b> 0 psi to 1,000 psi	<b>10000</b> 0 psi to 10,000 psi		
	<b>30/160</b> -30 inHg to 0 to 160 psi	<b>160</b> 0 psi to 160 psi	<b>1500</b> 0 psi to 1,500 psi	<b>15000</b> 0 psi to 15,000 psi		
	<b>30/200</b> -30 inHg to 0 to 200 psi	<b>200</b> 0 psi to 200 psi	<b>2000</b> 0 psi to 2,000 psi			
<b>SCALE OPTIONS</b>	<b>psi</b> psi single scale	<b>psi/kPa</b> psi/kPa dual scale	<b>psi/kg/cm<sup>2</sup></b> psi/kg/cm <sup>2</sup> dual scale	<b>psi/bar</b> psi/bar dual scale		
<b>CONNECTION SIZES</b>	<b>1/4</b> 1/4" NPT	<b>1/2</b> 1/2" NPT	<b>SST</b> SAE J1926-3:7/16-20 Adjustable			
<b>OPTIONS</b>	<b>CFF</b> Chrome Front Flange	<b>RF</b> Rear Flange	<b>GLO</b> Glass Lens Overlay	<b>ST</b> Stainless Steel Tagging		
	<b>CFFN</b> Chrome Front Flange w/o holes	<b>CCR</b> Chrome Cover Ring	<b>SGO</b> Safety Glass Overlay	<b>BT3</b> Brass Threaded Orifice 0.3 mm		
	<b>BFF</b> Brass Front Flange	<b>CBU</b> Chrome Bezel & U-Clamp	<b>AR</b> Adapter Ring	<b>BT4</b> Brass Threaded Orifice 0.4 mm		
	<b>BLFF</b> Black Front Flange	<b>MIP</b> Maximum Indicating Pointer	<b>LM</b> Laser Marking	<b>BT8</b> Brass Threaded Orifice 0.8 mm		
	<b>SSRF</b> 304SS Rear Flange	<b>LL</b> Polycarbonate Lens				


Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

NOTE: Refer to 300 Series Options & Accessories chart on page 51 for availability by part number.


**EXAMPLE**




**25-300**



**40-300**




**25-310**




# Dimensions

40-310





25-300 Front Flange





40-300 Front Flange

25-310 Front Flange




40-310 Front Flange


25-300 Rear Flange




## 40-300 Rear Flange




## 25-310 Rear Flange



## 40-310 Rear Flange



## 25-310 Chrome Triangular Bezel with U-Clamp



## 40-310 Chrome Triangular Bezel with U-Clamp

